



TOWER

SEALANTS

Technical Bulletin

2095 Memorial Park Road
Gainesville, Georgia 30504

Phone: 866-897-7568 or Fax: 866-897-7569

CAT-5 Elastomeric Patching Compound Textured Brush Grade

- **Permanent Flexible Fill**
- **Superior Paintability**
- **Interior / Exterior Use**
- **Water Clean Up**

Packaging: Gallon
Color: Off White
UPC Number: 843034000833
Product Code: TS-00083

Company Information:

Manufacturer: Tower Sealants, 2095, Memorial Park Rd., Gainesville, GA 30504

Customer Service: 866-897-7568

Fax Number: 866-897-7569

Website: www.towersealants.com

Product Description:

CAT-5 Brush Grade Elastomeric Patching Compound is extremely flexible with outstanding adhesive properties. It is uniquely formulated to provide a permanent repair for cracks and holes in above grade masonry and stucco surfaces.

Suggested Uses:

Ideal for filling and repairing recurring cracks and holes in above grade surfaces.

Substrates include but not limited to:

- **Plaster**
- **Stucco**
- **Masonry**

Surface Preparation:

- **Surface must be dry and free of dirt, dust, oil, mildew, loose paint, or other contaminates.**
- **Pressure wash with a 10% chlorine solution to achieve cleanliness.**

Application:

- Apply to hairline cracks with a clean brush and tool patch to desired finish before product dries.
- Knife grade Patch should be used for larger cracks These cracks should be chipped out to an even size and if greater than 1/2" in depth a non-gassing backer rod of the proper size should be inserted. When apply two or more layers allow to dry 24 hours between applications.
- Product is not sandable.
- Allow 24 hours before top coating.

For Best Results:

- Do not apply when temperatures are below 50°F or humidity is above 90%.
- Do not apply outside if rain is expected within 24 hours.
- Apply Masonry Surface Conditioner over the patched surfaces.
- Do not use below grade or under water.
- Keep from freezing.

Physical & Chemical Characteristics:

Vehicle:	Acrylic Latex
Volatile:	Predominately Water
Pigment:	Calcium Carbonate
Solids:	60% by weight
Weight per Gallon:	9.8 lbs.
Specific Gravity:	1.18
Service Temperature:	-30°F to 180°F
Temperature Application Range:	40°to 100° F
Freeze Thaw Stability:	DO NOT ALLOW TO FREEZE.
Flash Point:	None
Consistency:	Paste
Applications:	Interior / Exterior
Shelf Life:	12 months when stored at 50°F to 80°F
Odor:	Mild Sweet Acrylic
Drying Time:	Approximately 2 hours depending on environmental conditions.
Painting Time:	Overnight
MSDS No.:	

Clean up:

- Clean up hands and tools with soap and water.
- Store remaining product in a cool dry place with container lid closed and tightly sealed.

Safety:

- See Material Safety Data Sheet for safety information or product label.
- To request a Material Safety Data Sheet visit our web site at www.towersealants.com or call 866-897-7568

