



TOWER
SEALANTS

Technical Bulletin

2095 Memorial Park Road
Gainesville, Georgia 30504

Phone: 866-897-7568 or Fax: 866-897-7569

CAT-5 Elastomeric Patching Compound Textured Knife Grade

- **Permanent Flexible Fill**
- **Superior Paintability**
- **Interior / Exterior Use**
- **Water Clean Up**

Packaging: 1 Quart, 1 Gallon
Color: Off White
UPC Number: 843034000949, 843034000956
Product Code: TS-00094, TS-00095

Company Information:

Manufacturer: Tower Sealants, 2095, Memorial Park Rd., Gainesville, GA 30504

Customer Service: 866-897-7568

Fax Number: 866-897-7569

Website: www.towersealants.com

Product Description:

CAT-5 Knife Grade Elastomeric Patching Compound is extremely flexible with outstanding adhesive properties. It is uniquely formulated to provide a permanent repair for cracks and holes in above grade masonry and stucco surfaces.

Suggested Uses:

Ideal for filling and repairing recurring cracks and holes in above grade surfaces.

Substrates include but not limited to:

- **Plaster**
- **Stucco**
- **Masonry**

Surface Preparation:

- **Surface must be dry and free of dirt, dust, oil, mildew, loose paint, or other contaminants.**
- **Pressure wash with a 10% chlorine solution to achieve cleanliness.**

Application:

- **Fill hairline cracks with a clean putty knife and tool patch surface to desired finish before product dries.**
- **Larger cracks should be chipped out to an even size and if greater than 1/2" in depth a non-gassing backer rod of the proper size should be inserted. When apply two or more layers allow to dry 24 hours between applications.**
- **Product is not sandable.**
- **Allow 24 hours before top coating.**

For Best Results:

- **Do not apply when temperatures are below 50°F or humidity is above 90%.**
- **Do not apply outside if rain is expected within 24 hours.**
- **Apply Masonry Surface Conditioner over the patched surfaces.**
- **Do not use below grade or under water.**
- **Keep from freezing.**

Physical & Chemical Characteristics:

Vehicle: Acrylic Latex

Volatile: Predominately Water

Pigment: Calcium Carbonate

Solids: 65.7 by weight

Weight per Gallon: 10.48 lbs.

Specific Gravity: 1.258

Service Temperature: -30°F to 180°F

Temperature Application Range: 50° to 100° F

Freeze Thaw Stability: DO NOT ALLOW TO FREEZE.

Flash Point: None

Consistency: Paste

Applications: Interior / Exterior

Shelf Life: 12 months when stored at 50°F to 80°F

Odor: Mild Sweet Acrylic

Drying Time: Approximately 2 hours depending on environmental conditions.

Painting Time: overnight

MSDS No.:

Clean up:

- **Clean up hands and tools with soap and water.**
- **Store remaining product in a cool dry place with container lid closed and tightly sealed.**

Safety:

- **See Material Safety Data Sheet for safety information or product label.**
- **To request a Material Safety Data Sheet visit our web site at www.towersealants.com or call 866-897-7568**

