



Caulk Zero – Multi Purpose White

- FORMULA MADE WITH 25% RECYCLED MATERIAL
- ZERO VOC's*
- ZERO Glycols
- ZERO Phthalates
- ZERO Plasticizers

Packaging: 10.1 fl oz. (299 ml)
Product Code: TS-00000
UPC: 8430340000
Color: White

Company Information:

Manufacturer: Tower Sealants, 2095 Memorial Park Rd., Gainesville, GA 30504
 Customer Service: 866-897-7568
 Fax Number: 866-897-7569
 Website: www.towersealants.com

Product Description:

TOWER SEALANTS CAULK ZERO is a multi-purpose caulk. This product has Zero VOC's*. **TOWER SEALANTS CAULK ZERO** is manufactured and packaged with 25% post consumer recyclable materials and no added glycols, plasticizers or phthalates. It can be used on a wide variety of interior and exterior surfaces and has outstanding paintability.

The sealant forms a flexible, durable, airtight, water resistant seal that offers protection from environmental conditions. Once cured, the bead is mildew resistant and is designed to seal gaps, cracks, joints, and seams. **TOWER SEALANTS CAULK ZERO** is low odor and features soap and water clean-up.

Suggested Applications:

Windows	Trim	Penetrations
Doors	Sinks	Bathrooms
Counters	Siding	Flashings
Walls	Ceilings	Doors

Suggested Substrates:

Masonry	Brick	Laminates
Concrete	Wood	Aluminum
Painted Surfaces	Metal	PVC
Ceramic Tile	Marble	Glass

Performance Characteristics:

- Exceeds ASTM C-834, Type OP, Grade 0°C
- Interior or exterior use
- Paintable
- Weather resistant
- Cured bead is mildew resistant
- Cleans with soap and water
- VOC* 0%, Low odor

Caulk Zero – Multi Purpose White

Surface Preparation:

- Surface must be dry and free of dirt, dust, oil, mildew, loose paint, old caulk or other contaminants.
- Only apply when sealant surface and air temperature are above 40°F and rising.
- Do not apply on surfaces above 120° F or when rain is expected.

Application:

- Cut nozzle at a 45° angle.
- Properly designed joint not to exceed 1/2+in width.
- Use backer rod for joints deeper than 1/2+
- Tool or smooth bead within 10 to 15 minutes, depending on climatic conditions.
- Sealant maybe removed and tools cleaned prior to curing with soap and water.
- Depending on climatic conditions, allow 4 to 6 curing time prior to painting, full cure should occur 7-14 days after application.

Physical & Chemical Characteristics:

Vehicle:	Modified Acrylic, Siliconized
VOC's:	Non-chemically curing product, 0% (equivalent to 0 g/L)* * VOC content of this product is below the detection level of EPA 24. Levels below the detection level are reported as zero
Pigment:	Calcium Carbonate
Weight per Gallon:	13.75 ± 0.5
Specific Gravity:	Approximately 1.65
Service Temperature:	-25°F to 180°F
Temperature Application Range:	40°F and rising. Air temp no hotter than 95° and substrate not hotter than 120°F
Freeze Thaw Stability:	Passes 5 Cycles@ 0°F (1 cycle = 16hrs. @ 0°F, 8hrs at 75°F)
Flash Point:	None
Consistency:	10 to 30 G/S @ 75°F (SEMCO gun at 50psi)
Applications:	Interior / Exterior
Shelf Life:	24 months when stored at 50°F to 80°F
Coverage: 10.1 fl oz:	54 linear ft. at a 3/16+bead
Odor:	Mild Sweet Acrylic
Tooling Time:	10 to 15 Minutes
Tack Free Time:	60 Minutes

Clean up:

- Clean up hands and tools with soap and water.
- Clean up excess caulk with a damp cloth.

Safety:

- See Material Safety Data Sheet for safety information or product label.
- To request a Material Safety Data Sheet call 866-897-7568

SATISFACTION GUARANTEED: If not satisfied return used container and sales receipt to Tower Sealants LLC, Tech Service 2095 Memorial Park Rd Gainesville GA 30504 for sales price refund. Manufacturer shall not be held liable for damages in excess of the purchase price of the product. This is the sole and exclusive remedy and liability for defects or failure of this product.