



## LITE WALL LIGHTWEIGHT SPACKLING COMPOUND

- One Application
- Low Shrink Formula
- Interior/Exterior Use
- Fast Dry

Manufactured by:  
Tower Sealants, LLC  
2095 Memorial Park Road  
Gainesville, Georgia 30504  
Phone: 866-897-7568  
[www.towersealants.com](http://www.towersealants.com)

### Product Description:

**Tower Lite Wall Lightweight Spackling Compound** is a smooth, water-based, premixed product for use in patching holes, dents, scratches and other defects on interior or exterior substrates like wood, plaster, sheetrock, stucco or masonry. This advanced formula is easy to apply, tool and sand. **Lite Wall Lightweight Spackling Compound** features one application for most patching jobs.

### Performance Characteristics:

- Paint with acrylics immediately
- Repair cracks, dents and wall defects
- Interior / Exterior
- Ready to use

### Suggested Applications:

Stucco	Walls	Trim
EIFS	Cracks	Ceilings
Siding	Drywall	

### Suggested Substrates:

Masonry	Ceramic Tile	Wood
Concrete	Brick	Plaster

### Surface Preparation:

- Surface must be dry and free of dirt, dust, oil, mildew, loose paint, old caulk or other contaminants.
- Only apply when sealant surface and air temperature are above 40°F and rising.
- Do not apply on surfaces above 120°F or when rain is expected.

### Application:

- Mix thoroughly before use.
- Apply with a clean putty knife.
- One application in most cases. For repairs deeper than ¼" apply two or more layers allowing time to dry between applications, backer material may be required.
- Paintable within 5 minutes with latex paint.
- Allow to dry 2 to 4 hours before sanding.
- Allow 2 to 4 hours drying time before painting with oil-based products.

# LITE WALL LIGHTWEIGHT SPACKLING COMPOUND

## Physical & Chemical Characteristics:

Vehicle:	Styrene Acrylic Polymer Blend
VOC Less exempt solvents:	< 2.19%
Pigment:	Glass Micro Spheres
Solids:	Approximately 45%
Weight per Gallon:	3.6.0 ± 0.5
Specific Gravity:	Approximately 0.5
Service Temperature:	20°F to 120°F
Temperature Application Range:	40°F and rising. Air temp no hotter than 95° and substrate not hotter than 120°F
Freeze Thaw Stability:	Passes 5 Cycles@ 0°F (1 cycle = 16hrs. @ 0°F, 8hrs at 75°F)
Flash Point:	None
Consistency:	Light Paste
Applications:	Interior / Exterior
Shelf Life:	24 months when stored at 50°F to 80°F
Odor:	Mild Sweet Acrylic
Tooling Time:	10 to 15 Minutes
Tack Free Time:	5-10 Minutes
Full Cure:	2 to 4 Hours depending on conditions and amount used

## For Best Results:

- Not to be used on structural cracks.
- Exterior applications must be top-coated with good quality exterior paint.
- Do not use as a joint sealant where expansion and contraction might occur.
- Do not use as a skim coat for smoothing rough surfaces.
- Do not apply to surfaces where water ponding may occur.
- Keep from freezing.

## Clean up:

- Clean up hands and tools with soap and water.
- Clean up excess caulk with a damp cloth.

## Safety:

- See Material Safety Data Sheet for safety information or product label.
- To request a Material Safety Data Sheet call 866-897-7568

<b>Packaging:</b>	<b>1/2 Pint</b>	<b>1 Quart</b>	<b>1 US Gallon</b>
<b>Part:</b>	<b>TS-00154</b>	<b>TS-00178</b>	<b>TS-00161</b>
<b>Color:</b>	<b>White</b>	<b>White</b>	<b>White</b>
<b>UPC Number:</b>	<b>843034001540</b>	<b>843034001786</b>	<b>843034001618</b>