

## LITE WALL

### Lightweight Spackling

#### Product Description:

**Lite Wall** Lightweight Spackling is a smooth, water-based, premixed product for use in patching holes, dents, scratches and other defects on interior or exterior substrates like wood, plaster, sheetrock, stucco or masonry. This advanced formula is easy to apply, tool and sand. Lite Wall Lightweight Spackling features one application for most patching jobs. Available in gallon, quart, and half pint.

#### Performance Features:

- Repair cracks, dents and wall defects
- One application
- Low Shrinkage
- Excellent adhesion and durability
- Paint over immediately with acrylic
- Interior / Exterior
- Easy sanding
- Ready to use

#### Suggested Applications:

Stucco	Walls	Trim
EIFS	Cracks	Ceilings
Siding	Drywall	

#### Suggested Substrates:

Masonry	Ceramic Tile	Wood
Concrete	Brick	Metal

#### Surface Preparation:

Surfaces to be patched or repaired must be dry and free of all dirt, dust, oil, mildew, loose paint, old caulk or other contaminants. Only apply when sealant, surface, and air temperature are above 40°F and rising. Do not apply on surfaces that exceed 120°F, or when rain is expected.

#### Application:

Surface must be dry and clean, free of dust, dirt and old paint. Apply with a putty or broad knife and force into opening. For repairs deeper than ¼", apply two or more layers allowing time to dry between applications. Once dry, may be sanded with a fine or medium sand paper or sanding block. Paintable within 30 minutes with latex paint. For oil-based paint or if sanding is desired, allow to dry thoroughly for 2 to 4 hours. Exterior applications must be top coated with good quality exterior paint. Do not use as a skim coat or as a joint sealant where excessive movement could occur. Do not apply to surfaces where ponding water could occur. Do not use when temperature is below 40°F. Clean tools with soap and water. Keep container tightly sealed. **KEEP FROM FREEZING.**

*Continued Next Page*

#### Product Specifications

<b>Vehicle:</b>	Styrene Acrylic Polymer Blend
<b>VOC:</b>	<2.19%
<b>Pigment:</b>	Glass Micro Spheres
<b>Solids:</b>	Approximately 45%
<b>Weight per Gallon:</b>	3.5 ± 0.5
<b>Specific Gravity:</b>	Approximately 0.5
<b>Service Temp:</b>	20°F to 120°F
<b>Temp Application Range:</b>	40°F and rising. Air temp no hotter than 95° and substrate not hotter than 120°
<b>Freeze Thaw Stability:</b>	Passes 5 Cycles@ 0°F (1 cycle = 16hrs. @ 0°F, 8hrs at 75°F)
<b>Flash Point:</b>	None
<b>Consistency:</b>	Light Paste
<b>Applications:</b>	Interior / Exterior
<b>Shelf Life:</b>	24 months when stored at 50°F to 80°F
<b>Odor:</b>	Mild Sweet Acrylic
<b>Tooling Time:</b>	10 to 15 Minutes
<b>Tack Free Time:</b>	5-10 Minutes
<b>Paint Over Time:</b>	30 minutes to 4 hours

<b>Color:</b>	White
<b>Item Number:</b>	
½ Pint:	TS-00154
1 Quart:	TS-00178
1 US Gallon:	TS-00160
<b>UPC Code:</b>	
½ Pint:	843034001540
1 Quart:	843034001786
1 US Gallon:	843034001601

## LITE WALL – (cont.)

---

### Clean Up:

Immediately after use, clean uncured material and tools with soap and water. Remove cured sealant by cutting with a sharp-edged tool.

**WARNING!** IRRITATING TO SKIN, EYES AND RESPIRATORY TRACT. Harmful if swallowed, inhaled or absorbed through the skin. May cause allergic skin reactions and/or central nervous system depression. Adverse reproduction effects have been reported in animals. May cause adverse kidney effects. Avoid contact with eyes, skin and clothing. Use in well ventilated area. Wear eye, skin, and respiratory protection. Eye contact: Immediately flush with water for 15 minutes and get medical attention immediately. If swallowed: Do not induce vomiting. Give large quantities of water and get medical attention. Never give anything by mouth to an unconscious person. For health information, refer to Material Safety Data Sheet or call Chemtrec at 800-424-9300. **KEEP OUT OF REACH OF CHILDREN.**

**⚠WARNING!** Cancer and Reproductive Harm – Go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov) for additional information

---

### First Aid:

In case of skin contact, wash off quickly with plenty of soap and water and remove contaminated clothing. For eye contact, flush eyes immediately with large quantities of water for at least 15 minutes. If swallowed, obtain medical treatment immediately. **DO NOT INDUCE VOMITING.** If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, seek medical help.

Material Safety Data Sheets (SDS) available upon request via [towersealants.com](http://towersealants.com) or by calling 866-897-7568

Distributed by Tower Sealants, Gainesville, GA. 30504 – Made in U.S.A

**Product Replacement Policy:** After proper storage and application, if this product cracks, peels or crumbles, manufacturer will replace the product if purchaser returns proof of purchase to manufacturer. Manufacturer shall not be held liable for damages in excess of the purchase price. This is the sole and exclusive remedy and liability for defects or failure of this product. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESSED OR IMPLIED; INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS.