SAFETY DATA SHEET



Date of issue/Date of revision

Version 2

05 November 2018

Section 1. Identification

Product name : Tower Silicone Sealant Clear

Product code : Acetoxy Silicone Clear

Other means of identification

: Caulk, Sealant

Product type : Paste

Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications.

Use of the substance/

mixture

: Caulking, Sealing

Uses advised against : Not applicable.

Supplier : Tower Sealants

2095 Memorial Park Road Gainesville, GA 30504

Emergency telephone

number

: Chemtrec: 1-800-424-9300

Technical Phone Number : 1-770-535-8782 (8:00 am to 5:00 pm EST)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 3 SKIN CORROSION/IRRITATION - Category 1B

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 13%

GHS label elements







Hazard pictograms

Signal word : Danger

United States Page: 1/12

Date of issue 11 September 2018 Version 2

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 2. Hazards identification

Hazard statements

- : Toxic if swallowed.
- : Causes severe skin burns and eye damage.
- :May cause respiratory irritation.

Precautionary statements

Prevention

: Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Avoid breathing dust. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Response

: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Storage

: Store locked up.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.

Hazards not otherwise classified

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture

: Mixture

Product name

: TOP GUN 350 SILICONE SEALANT CLEAR

Ingredient name	%	CAS number
Siloxanes and Silicones, di-Me, hydroxy-terminated	40 - 70	70131-67-8
Distillates (petroleum), hydrotreated middle	3 - 7	64742-46-7
Methylsilanetriyl Triacetate	1 - 5	4253-34-3
Triacetoxyethylsilane	1 - 5	17689-77-9

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

United States Page: 2/12

Date of issue 11 September 2018 Version 2

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person. **Description of necessary first aid measures**

Eve contact : Check for and remove any contact lenses. Immediately flush eyes with running water for

at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser. Do NOT use solvents or thinners.

: If swallowed, seek medical advice immediately and show this container or label. Keep Ingestion

person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eve contact : Causes serious eye damage. Inhalation : May cause respiratory irritation.

Skin contact : Causes severe burns. Defatting to the skin.

Ingestion : Toxic if swallowed. May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

> suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

United States Page: 3/12

Date of issue 11 September 2018 Version 2

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 4. First aid measures

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: No specific fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

> **United States** Page: 4/12

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 6. Accidental release measures

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

United States Page: 5/12

Date of issue 11 September 2018 Version 2

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 8. Exposure controls/personal protection

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection : Chemical splash goggles and face shield.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

nitrile neoprene

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Paste
Color : Clear
Odor : Acetoxy
Odor threshold : Not available.
PH : Not available.
Melting point : Not available.
Boiling point : Not available.

Flash point : Closed cup: >93.33°C (>200°F)

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Flammability (solid, gas) : Not available.

United States Page: 6/12

Date of issue 11 September 2018 Version 2

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 9. Physical and chemical properties

Lower and upper explosive

(flammable) limits

: Not available.

Evaporation rate

: 0.09 (butyl acetate = 1)

Vapor pressure

: 0 kPa (0 mm Hg) [room temperature]

Vapor density

: Not available.

Relative density

Density (lbs / gal)

: 0

Solubility

Insoluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not available.

Viscosity

: 1-10 g/s

Volatility

: 7% (v/v), 7% (w/w)

% Solid. (w/w)

: 93

Section 10. Stability and reactivity

Reactivity

: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid

: When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials

: Keep away from the following materials to prevent strong exothermic reactions: oxidizing

: Decomposition products may include the following materials: carbon monoxide, carbon dioxide,

agents, strong alkalis, strong acids.

Hazardous decomposition products

smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Methylsilanetriyl Triacetate Triacetoxyethylsilane	LD50 Oral LD50 Oral	Rat Rat	2060 mg/kg 1.462 g/kg	-

Conclusion/Summary

: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.

United States Page: 7/12

Date of issue 11 September 2018 Version 2

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 11. Toxicological information

Respiratory: There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin : There are no data available on the mixture itself.Respiratory : There are no data available on the mixture itself.

<u>Mutagenicity</u>

Conclusion/Summary: There are no data available on the mixture itself.

<u>Carcinogenicity</u>

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Name	Category
Siloxanes and Silicones, di-Me, hydroxy-terminated	Category 3
Methylsilanetriyl Triacetate	Category 3

Specific target organ toxicity (repeated exposure)

Not available.

Target organs : Contains material which causes damage to the following organs: brain, central nervous

system (CNS).

Contains material which may cause damage to the following organs: upper respiratory

tract, eyes.

Aspiration hazard

Name	Result	
Distillates (petroleum), hydrotreated middle	ASPIRATION HAZARD - Category 1	

Information on the likely routes of exposure

Potential acute health effects

Eye contactInhalationCauses serious eye damage.May cause respiratory irritation.

Skin contact: Causes severe burns. Defatting to the skin.

Ingestion: Toxic if swallowed. May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

United States Page: 8/12

Date of issue 11 September 2018 Version 2

Product name TOP GUN 350 SILICONE SEALANT CLEAR

Section 11. Toxicological information

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness dryness cracking

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary

There are no data available on the mixture itself. Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater hearing loss than expected from exposure to noise alone. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate

Potential delayed effects

effects

: There are no data available on the mixture itself.

: There are no data available on the mixture itself.

Long term exposure

Potential immediate

effects

There are no data available on the mixture itself.

Potential delayed effects: There are no data available on the mixture itself.

Potential chronic health effects

General

: Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or

dermatitis.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value		
Oral	120.9 mg/kg		

United States Page: 9/12

Product code TT Silicone

Date of issue 05 November 2014 Version 1

Product name Tower Acetoxy Silicone Clear

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (K_{oc})

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

United States Page: 10/12

Product code TT Silicone

Product name Tower Acetoxy Silicone Clear

14. Transport information

Additional information

DOT : None identified.IMDG : None identified.IATA : None identified.

Special precautions for user

: **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

Section 15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.
Australia inventory (AICS) : All components are listed or exempted.
Canada inventory (DSL) : All components are listed or exempted.
China inventory (IECSC) : All components are listed or exempted.

Europe inventory (REACH): Please contact your supplier for information on the inventory status of this material.

Japan inventory (ENCS) : Not determined.

Korea inventory (KECI)
 New Zealand (NZIoC)
 All components are listed or exempted.
 Philippines inventory (PICCS)
 All components are listed or exempted.

United States

U.S. Federal regulations :

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

California Prop 65: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

SARA 311/312

Classification : Immediate (acute) health hazard

Composition/information on ingredients

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Siloxanes and Silicones, di-Me, hydroxy-terminated	No.	No.	No.	Yes.	No.
Distillates (petroleum), hydrotreated middle	No.	No.	No.	Yes.	No.
Methylsilanetriyl Triacetate Triacetoxyethylsilane	No. No.	No. No.	No. No.	Yes. Yes.	No. No.

United States Page: 11/12

Product code TT Silicone

Date of issue 05 November 2018 Version 2

Product name Tower Acetoxy Silicone Clear

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 3 Flammability: 1 Physical hazards: 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 3 Flammability: 1 Instability: 0

Organization that prepared : EHS

the MSDS

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Tower Sealants, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 12/12