

ADVANCED ALL-WEATHER TECHNOLOGY

FEATURES AND BENEFITS:

- All-Weather application
- Apply on damp surfaces
- Can be applied between 21°F and 120°F
- Rapid cure - water & paint ready in 1 hour
- Will not shrink
- Excellent Adhesion
- Resistant to most chemicals
- Adheres to Kynar® and other specialty metal coatings

SUBSTRATES:

- Concrete
- Masonry
- Stucco
- Glass
- Metal
- Building Wraps
- Fascia
- Flashing



SPECIFICATIONS:

- ASTM C-920 Type S, Grade NS, Class 25
- ASTM C-834 -18°C
- Fed Spec TTS-00230C
- Meets performance requirements of:
 - AAMA 808.3
 - 805.2
 - 803.36 (Type I)
 - 802.3 (Type II)

USES:

- Expansion & control joints
- Concrete panel joints
- Windows, doors & siding
- Tilt-wall joints
- Precast units
- EIFS



TS-00468



TS-00464



HIGH-PERFORMANCE. ALL-WEATHER. PERMANENT PROTECTION.



AU-1™ Hybrid Construction Sealant is a **single-component, Silyl-terminated Polyether Elastomeric Sealant** engineered for maximum adhesion, flexibility, and durability.

- **Versatile Application** – Bonds to most common building substrates, even in damp or moisture-prone areas.
- **All-Weather Performance** – Apply in any condition; designed to maintain adhesion and flexibility in the harshest climates.
- **Long-Lasting Protection** – Once cured, it is mildew resistant, UV stable, and forms a permanent waterproof seal.
- **Low VOC Formula** – Contributes to cleaner, healthier work environments.

AU-1 Hybrid delivers in all climates and conditions.

Available in 10.1 fl. oz. Cartridges and 20 oz. Sausages in White



TS-00468

BACK

AU-1™ HYBRID COMMERCIAL CONSTRUCTION SEALANT

7 07 92 00
Joint Sealants

**HIGH-PERFORMANCE. ALL-WEATHER.
PERMANENT PROTECTION.**



AU-1™ Hybrid Construction Sealant is a **single-component, Silyl-terminated Polyether Elastomeric Sealant** engineered for maximum adhesion, flexibility, and durability.

- **Versatile Application** – Bonds to most common building substrates, even in damp or moisture-prone areas.
- **All-Weather Performance** – Apply in any condition; designed to maintain adhesion and flexibility in the harshest climates.
- **Long-Lasting Protection** – Once cured, it is mildew resistant, UV stable, and forms a permanent waterproof seal.
- **Low VOC Formula** – Contributes to cleaner, healthier work environments.

AU-1 Hybrid delivers in all climates and conditions.

Available in 10.1 fl. oz. Cartridges and 20 oz. Sausages in White



TS-00468

FRONT

AU-1™ HYBRID COMMERCIAL CONSTRUCTION SEALANT

7 07 92 00
Joint Sealants

ADVANCED ALL-WEATHER TECHNOLOGY

FEATURES AND BENEFITS:

- All-Weather application
- Apply on damp surfaces
- Can be applied between 21°F and 120°F
- Rapid cure - water & paint ready in 1 hour
- Will not shrink
- Excellent Adhesion
- Resistant to most chemicals
- Adheres to Kynar® and other specialty metal coatings

SUBSTRATES:

- Concrete
- Masonry
- Stucco
- Glass
- Metal
- Building Wraps
- Fascia
- Flashing



SPECIFICATIONS:

- ASTM C-920 Type S, Grade NS, Class 25
- ASTM C-834 -18°C
- Fed Spec TTS-00230C
- Meets performance requirements of:
 - AAMA 808.3
 - 805.2
 - 803.36 (Type I)
 - 802.3 (Type II)

USES:

- Expansion & control joints
- Concrete panel joints
- Windows, doors & siding
- Tilt-wall joints
- Precast units
- EIFS



TS-00468



TS-00464

For product information or samples call: 866.897.7568
For tech support email: tech@towersealants.com
Online at: www.towersealants.com



STS9166

AU-1 Hybrid Sales Flyer_STS9166
Size w/bleed - 8.75" w x 11.125"h
Trim Size - 8.5"w x 11"h
Material - 100# Text Gloss
Colors - 4c/4c

Black	PMS 186C	PMS Warm	White
C-0	C-12.46	Gray 1C	C-0
M-0	M-100	C-15	M-0
Y-0	Y-91.29	P-14	Y-0
K-100	K-3.08	Y-17	K-0