



AU-1

BUILDING ENVELOPE SYSTEM

Protect your build with one integrated moisture management system designed for speed, durability, and long-term performance.



AU-1 LAB™

LIQUID-APPLIED AIR, WATER, AND FLASHING BARRIER

A High-Performance SBR that cures to an elastomeric weather-resistive barrier and flashing membrane. This unique, dual-purpose formulation is designed to create a seamless durable layer of protection.

2-IN-1 SOLUTION:

- ✓ Air & Water Barrier
 - Apply as monolithic barrier for use as a building envelope
- ✓ Liquid-Applied Flashing
 - Apply around rough openings as moisture mitigation for wind-driven rain

Meets performance requirements

AAMA 714-22

Tested in accordance with performance requirements of **ABAA** for WRB materials



AU-1 COMMERCIAL CONSTRUCTION SEALANT

Acrylic Urethane technology designed to outperform polyurethanes, hybrids, and silicones in waterproofing applications and window installations.


- ✓ Robust UV Inhibitor package
- ✓ No Plasticizers = No loss of flexibility, no shiners
- ✓ Easier application
- ✓ Industry-leading durability
- ✓ Eliminates need for solvents on jobsite
- ✓ ASTM C-920 Class 35
- ✓ Also available in AU-1 Hybrid for wet/cold applications

7 07 92 00
Joint Sealants



INSTALLATION IN **FOUR SIMPLE STEPS**

1 PREP



Start with a clean, dry surface. Fill gaps between $\frac{1}{4}$ and $\frac{1}{2}$ inch with **AU-1 Construction Sealant**.

Gaps under $\frac{1}{4}$ inch require no prep—simply flood coat during application.

2 APPLY



Apply **AU-1 LAB** with a brush, roller, or standard airless sprayer.

Recommended method for broad wall application is to spray in a crosshatch pattern. Use a mil gauge to ensure a minimum of 30 wet mils is applied for a water-tight seal.

3 INSPECT



Inspect the surface and touch up as needed to create a smooth, uniform, pinhole-free membrane.

4 FINISH



Clean tools with soap and water before product dries.

Once cured, install your exterior cladding or stucco within six months. **AU-1 LAB** is self-sealing around fasteners, and stucco can be applied directly over it—no primer required.



SCAN FOR
INSTALLATION GUIDE, TECHNICAL DATA
SHEETS, & ARCHITECTURAL SPECIFICATIONS

For product information or samples call: 866.897.7568
For tech support email: tech@towersealants.com
Online at: www.towersealants.com



TOWER
SEALANTS

08/26 STS9180